



Fecon Drills

Geothermal Series

GL14 Support Trailer



JOBSITE EFFICIENT

**TOWABLE BY TRUCK OR FECON GL300 DRILL RIG
GROUT/MUD MIXING AND PUMPING WORK PLATFORM
TOOL & BIT STORAGE**



fecon.com
sales@fecon.com
+1 513 696 4430
800 528 3113
fax 513 696 4431

The GL14 Support Trailer is a self-contained Grouting and/or Mud Drilling support system for your drilling applications. The GL14 is an efficient work station for the grout, mud mixing and pumping operations. Ramps for curbside or jobsite use provide safe easy access when handling bagged mixes. The water system allows for back flushing & cleaning. The Fecon GL300 Drill and GL14 Support Trailer together provide "The Hole Solution" for geothermal ground loop installation.

GL14 Features:

- Lockable Storage for Tools and Drill Rods
- 200 gal Water Supply Tank
- 500 ft Grout Line Hose Reel Capacity
- Towable by the Fecon GL300 Drill Rig
- 4-Wheel Brakes for Safe Highway Towing
- Grated Metal Walkways for Safe Footing



GL14 Trailer Specifications

6' x 14' Flat Bed	7,000 lb GVWR Dual Axle	Lockable Tool Storage
Towing - 213"L x 96"W x 67"H	200 Gal. Tank w/ 2 Inline Mixing Nozzles	4-Wheel Electric Brakes
Operating - 261"L x 144"W x 67"H	Side & Rear Ramp Gates w/ Lift Assist	2" Ball Hitch



GB580 Grout Boy

13 HP Honda Electric Start Engine
58 Gallon Mixing Capacity Hopper
3L6 Progressive Cavity Grout Pump
18 gpm and 225 psi
Self-contained Hydraulic System
Variable Speed Control Valves
Skid Frame - 60" x 40" x 51"



MB300 Mud Boy

2" Mud Pump
15 gal Round Mixing Hopper w/ Cone-Shaped Bottom
Mixing Action: Venturi / Recirculation
2" Hose and Valves
3 Gallon Antifreeze Tank
High Pressure Low Volume Mud Pump for Down Hole Mud



HR500 Hose Reel

Variable Speed Control Valve for Winding
Hose Reel Cap. - 500' 3/4" or 300' 1" Hose

• Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
 • Weights may vary based on options. • Specifications subject to change without notice.
 • Safety Is The Responsibility Of The Operator.

