



Stump Grinders

Stump Hog Forestry Attachments





fecon.com
sales@fecon.com
+1 513 696 4430

SH260

- Grind out entire root balls with 26" diameter grinding.
- Sweep left to right.
- Severe Duty frame, wheel and drive components.
- Backfill blade for filling the hole and leveling chips.
- Attaches to the universal skid steer mount.
- Plug in the high flow lines, case drain and low flow lines on carriers that are equipped.
- 12" Telescoping capability.
- Easily tilt up and down with joystick controls.
- Interchangeable with Fecon Mulcher.

General	
Hydraulics Horsepower	70 - 100 hp
Flow / PSI	30-45 @ 3000 - 4750 psi
Wheel Diameter x Thickness	26" x 3 3/4"
Work Zone	70" w x 24" d
Ground Clearance	15"
Weight	1640 lbs
Dimensions	63" l x 60" w
Number of Teeth	32

SH360

- Just 15 Tools with single bolt fastening.
- Three tool choices for lower operating costs.
- Unlimited swing, reach and depth for the hard to reach stumps that cannot be safely accessed with a traditional stumper.
- Wheel supported on both sides.
- Interchangeable with Fecon Mulcher.
- Removable guard installed for when working in sensitive areas.
- Polychain belt drive.
- Bolt on mount custom to excavator with pin-on or quick attach options.

Technical Specifications		
Model	Excavator Size	Hydraulic Flow
Weight / Wheel Diameter (lbs / in)		2600 lbs / 36"
SH360-45	20 - 30 ton	40-55 gpm
SH360-61	33 ton and higher or BHP170 on 12 ton or higher	60-80 gpm
SH360-100	BHP250	100 - 120 gpm

SH400

- SH400 provides one function, to swing RH / LH.
- Made-to-order mount incorporated into the stumper structure, mount is to be positioned for optimum wheel-to-stump geometry.
- Central pivot with tapered roller bearings.
- Drive motor is a 160cc axial piston, Sunstrand series 90 which offers a rotor speed of approximately 500 rpm.
- 1 1/4" hoses plumbed easily to bulkhead.
- Backfill blade for filling the hole and post cutting soil movement.
- Backfill blade also acts as a rest for the SH400 in an upright position after disengagement from carrier.
- Interchangeable with Fecon Mulcher.

General	
Hydraulics Horsepower	170 - 350 hp
Flow / PSI	65 - 140 gpm @ 5500 psi
Wheel Diameter x Thickness	40" x 1 1/2"
Work Zone	84"
Weight	4550 lbs
Number of Teeth	72

- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
- Always insure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection meet your job safety requirements.
- Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
- Weights are subject to vary based on options. • Safety Is The Responsibility Of The Operator.
- Specifications subject to change without notice. • Pictures may contain optional accessories.
- Photographs may have been altered for marketing purposes.



GS-30F-0019S