



# Excavator Attachments

## Reach Your Excavator's Potential

**Bull Hog® Mulchers • Stump Grinders  
Tree Shears • Power Packs**



# Bull Hog

# Excavator



## FEATURES

- Heavy or Severe Duty Models
- Low Maintenance Design
- Exceptional Tool Life
- Stout Rotor and Body
- The most durable mulcher on the market!
- Bull Hog Excavator Mulchers for 5 - 45 Ton Excavators
- Power Pack Not Required
- Three Rotor Choices - FGT, HDT or DCR
- Several Tool Choices per Rotor
- Fixed Displacement or Variable Displacement Motors
- Priority Valve Recommended for Some Excavators

### FGT



SAMURAI KNIFE (FLIPABLE)    STANDARD DUTY    SEVERE DUTY    STONE TOOL

### DCR



SAMURAI KNIFE (FLIPABLE)

### HDT



SINGLE CARBIDE    STANDARD DOUBLE CARBIDE    STONE/ROCK    CHIPPER KNIFE

TYPE	MODEL	WORKING WIDTH	OVERALL WIDTH	APPROX WEIGHT	APPROX FLOW RANGE	EXC SIZE (METRIC TON)	TOOLS
Heavy Duty	FMX36*	36" / 914 mm	44" / 1118 mm	850 lb / 386 kg	12 - 40 gpm	5 - 10 T	18
Heavy Duty	FMX50*	50" / 1270 mm	58" / 1473 mm	1050 lb / 476 kg	12 - 40 gpm	5 - 10 T	22
Heavy Duty	CEM36	36" / 914 mm	52" / 1321 mm	1475 lb / 669 kg	17 - 30 gpm	7 - 15 T	18
Heavy Duty	BH47EXC	37" / 940 mm	50" / 1270 mm	2850 lb / 1293 kg	27 - 65 gpm	12 - 20 T	18
Heavy Duty	BH62EXC	50" / 1270 mm	63" / 1600 mm	3240 lb / 1470 kg	27 - 65 gpm	15 - 20 T	24
Severe Duty	BH40EXC	36" / 914 mm	51" / 1295 mm	3675 lb / 1667 kg	30 - 105 gpm	15 - 45 T	18
Severe Duty	BH80EXC	56" / 1422 mm	72" / 1828 mm	4275 lb / 1939 kg	38 - 105 gpm	20 - 45 T	30
Severe Duty	BH200EXC	59" / 1499 mm	77" / 1956 mm	5300 lb / 2358 kg	40 - 180 gpm	20 - 45 T	30

\*FMX models only available with split ring rotor and Cubit Knife

CEM36 & FMX listed weight includes typical mount and both come standard with a variable displacement hydraulic motor. All other models can be equipped with variable displacement or fixed displacement hydraulic motors.

\*Weights listed for EXC models will vary based on hydraulic motor choice and options & do not include weight of the mount.

# BHP

# Power Packs

## FEATURES

- Equipped with Fecon Power Management®
- Dramatically Improves Engine Response/Recovery
- Sustained Peak Grinding Power
- Reduced Fuel Consumption
- Optimized Operator Feedback
- Limited Stalling
- Quicker Recovery
- Maximized Productivity
- Modular Design for BHP270

Mulch Brush, Branches, Slash, Standing and Fallen Trees, Root Balls and Stumps faster and more effectively than before!



Bull Hog Excavator Mulchers are most often powered by the excavator's hydraulic system. However, when absolute maximum productivity is required a Bull Hog Power Pack provides the ultimate solution.

COMMON EXC SIZE	MODEL	ENGINE	BULL HOG	STUMP HOG
12 - 20 Ton	BHP170	170 hp Cummins	BH62EXC/BH40EXC	SH360-61
20 - 30 Ton	BHP270	270 hp Cummins	BH80EXC/BH200EXC	SH360-100

## APPLICATIONS

- R.O.W.
- Land Clearing
- Control Invasive Species
- Orchard Clean-up and Removal
- Prairie and Wetland Restoration
- Agricultural Land Reclamation
- Wild Fire Maintenance

## Excavator Bull Hog®

### Heavy Duty

- 5-10 Ton Excavators
  - FMX36 and FMX50
- 7-25 Ton Excavators
  - CEM36, BH47EXC and BH62EXC
- Variable Displacement Motor Options

### SEVERE Duty

- **3/4"** Steel Body Construction
- BH40EXC, BH80EXC and BH200EXC
- 15 - 45 Ton Excavators
- SEVERE Duty Bearings
- Variable Displacement Motor Options



### Mounts

- Quick Attach or Pin-On
- Easily Change Mounts for Different Excavators with the Bolt-on Interface

### Rotor Exposure

- Cut Through Standing Trees
- Mulch Slash Piles
- Grind to the Surface



**fecon.com**  
**sales@fecon.com**  
**+1 513 696 4430**

## Stumpex

- No Carbide Tools to Replace
- Any Species of Wood
- Bores 20" into Ground while Cutting Feeder Roots

Model	Weight	Min - Max Flow	PSI	Excavator Size
Stumpex	1368 lb / 621 kg	20 - 42 gpm	4000	8-12 Ton

\* Excavators must have reverse flow



## Stump Hogs

- Unlimited swing, reach and depth for the hard to reach stumps that cannot be safely accessed with a traditional stump er
- Just 15 Tools with single bolt fastening
- Wheel supported on both sides
- Interchangeable with Fecon Mulcher
- Guard (removable) for working in sensitive areas.
- Polychain belt drive
- Bolt on mount custom to excavator with pin-on or quick attach options
- Three tool choices for lower operating costs

Model	Weight	Min - Max Flow	Wheel Diameter	Excavator Size
SH360-45	2500 lb / 1134 kg	40 - 50 gpm	36"	20 - 30 ton
SH360-61	2500 lb / 1134 kg	50 - 64 gpm	36"	33 ton and higher or BHP170 on 12 ton or higher
SH360-100	2600 lb / 1179 kg	95 - 105 gpm	36"	BHP250



## Tree Shears

- Fecon offers models for excavators 7 ton and up. Requires as little as 20 gpm of Low Flow Hydraulics.
- Great for reaching up and down slopes and areas that are otherwise inaccessible.
- Provided with Fecon "H" mounting bracket and bolt-on hanger bracket sized to the Excavator.
- AR400 Shear knives.

General	FBS1200EXC	FBS1400EXC	FBS1500EXC	FBS1600EXC
Height	64"	64"	70"	72"
Width	50"	48"	64"	62"
Depth	40"	42"	46"	67"
Weight	1250 lbs.	2000 lbs.	2100 lbs.	3700 lbs.
Cutting Capacity Diameter	12"	14"	15"	16"
Grabber Arm Cylinder	2x10 (2)	3x10	3x10 (2)	3.5x10
Accumulator Arm Cylinder	2x10	2.5x10	2.5x10	3.5x9.5
Knife Cylinder	4x8 (2)	5x14 (1)	5x12 (2)	6x14 (1)
Knife Action	Double	Single	Double	Single
Excavator Size	7-8 Ton	8-12 Ton	8-12 Ton	12-16 Ton
Hydraulic Flow Require.	15-20 gpm	20-25 gpm	20-25 gpm	25-35 gpm
Hydraulic Pressure Require.	3000 psi	3000 psi	3000 psi	2500-3500 psi



- Operators cab must be protected with both properly maintained 1/2" LEXAN® Glass (or equal) and Falling Object Protection.
- Always insure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection) meet your job safety requirements.
- Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
- Weights may vary based on options.
- Safety Is The Responsibility Of The Operator. • Specifications subject to change without notice.
- Pictures may contain optional accessories. • Photographs may have been altered for marketing purposes.



GS-30F-0019S