

MAKE IT HAPPEN

FECON®



BLACKHAWK®

fecon.com

800 528 3113

sales@fecon.com

+1 513 696 4430

Whether you are buying, renting, or servicing your mulching equipment, FECON has solutions that focus on your success. Operator driven design with a global network that is woven into every product.



- Certain guarding and features may have been removed for illustrative purposes.
- ALWAYS RUN WITH PROPER GUARDING IN PLACE.
- Weights may vary based on options.
- Specifications subject to change without notice.
- Photographs may have been altered for marketing purposes.
- SAFETY IS THE RESPONSIBILITY OF THE OPERATOR.
- Always ensure your carrier's safety features, including ROPs & FOPs, meet your job safety requirements.
- Pictures may contain optional accessories.

BHKR_102021

BLACKHAWK®

FECON®



FORESTRY MULCHER

[FECON.COM](https://fecon.com)

800 528 3113

BLACKHAWK® SPECIFICATION

GENERAL		
Model	BK7618	BK6218
Working Width	76"	62"
Overall Width	91"	76"
Weight	2,980 lbs	2600 lbs
Flow Range	30 - 45 gpm	30 - 45 gpm
Max Pressure	6,000 psi	6,000 psi
Max Horsepower	120 hp	120 hp
Number of Tools	30	24
Rotor Diameter	18"	18"
Rotor Speed	2,400 rpm	2,400 rpm
Rotor Bearing Size (mm)	ST65	ST65
Motor(s)	1 x 107V	1 x 107V

BUILT FOR LIFE ENGINEERED FOR SUCCESS

The BLACKHAWK® mulcher tackles vegetation management and land clearing needs in stringy, fibrous, dense, and fast-growing material typically found in regions with higher temperatures and longer growing cycles.

The BLACKHAWK® mulcher is designed to quickly process stubborn standing and felled vegetation, ensuring no unprocessed material is left behind.

PERFORMANCE

- ✦ Utilizing shear bars and knife tools, the BLACKHAWK® creates consistent chips on the first pass
- ✦ The cutting chamber is designed to process material going forwards and back dragging without leaving unprocessed material
- ✦ 18" rotor spools up quickly and minimizes wait time

EFFICIENCY

- ✦ Compact body design and increased visibility improves carrier operating and handling
- ✦ Broadcasting front discharge mitigates the need for multiple passes
- ✦ Simplified hydraulic system minimizes heat generation

DURABILITY

- ✦ Replaceable bolt-on shear bar and wear liner
- ✦ Rotate to increase life
- ✦ High strength steel body construction to withstand the rigors of everyday use
- ✦ Adjustable pin-on push bar to guide cut material

OPTIONAL ADD ONS:

FECON® Hydraulic Cooler

Designed to be mounted on CTL and Skid Steer to maintain the hydraulic fluid at optimal temperature and viscosity.

FECON® Polycarbonate Door

Form-fit 1/2" polycarbonate door required for mulching applications. Our replacement windows are formed to duplicate the OEM glass shape.

