

FECON[®]

Roof Mounted Hydraulic Cooler

- All steel design weighing about 200 lbs plus mounting brackets
- Universal mounting rails
- Tool-less hinged lid
- Tool-less removable intake screen
- Two 11" electric fans on a temperature switch
- Dimensions: 22" Wide x 40" Long x 13" Tall
- Cooling capacity up to 120,000 BTU/hour
- Flow up to 48 GPM
- 65 PSI bypass relief for cold oil starts
- Order basic cooler kit or CTL specific kit



COOLER INSTALL

- Mount cooler to the top of the cab
- Check loader arm clearance and cab tilt
- Plumb cooler in series before CTL cooler
- Wire fans and temperature switch to battery relay



FECON[®]

fecon.com • sales@fecon.com
800 528 3113 • +1 513 696 4430



- Operators cab must be protected with both properly maintained 1/2" LEXAN[®] Glass (or equal) and Falling Object Protection.
- Always insure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection) meet your job safety requirements.
 - Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
- Weights may vary based on options. • Safety Is The Responsibility Of The Operator. • Pictures may contain optional accessories
 - Specifications subject to change without notice. • Photographs may have been altered for marketing purposes.