

MAKE IT
HAPPEN

FECON®



BLACKHAWK®

fecon.com
800 528 3113

sales@fecon.com
+1 513 696 4430



Whether you are buying, renting,
or servicing your mulching
equipment, FECON has solutions
that focus on your success.
Operator driven design with a
global network that is woven into
every product.

- Operators cab must be protected with both properly maintained 1/2" Polycarbonate Glass (or equal) and Falling Object Protection.
- Certain guarding and features may have been removed for illustrative purposes, always run with proper guarding.
- Weights may vary based on options.
- Specifications subject to change without notice.
- Photographs may have been altered for marketing purposes.
- Always insure that your carrier manufacturers safety features (including Falling Object Protection, and Roll-Over Protection) meet your job safety requirements.
- SAFETY IS THE RESPONSIBILITY OF THE OPERATOR.
- Pictures may contain optional accessories

BHKY_102021

BLACKHAWK®

FECON®



FORESTRY
MULCHER

FECON.COM

800 528 3113

BLACKHAWK® SPECIFICATION

GENERAL	
Model	BK7618V
Working Width	76"
Overall Width	91"
Weight	2,840 lbs
Flow Range	30 - 45 gpm
Max Pressure	6,000 psi
Max Horsepower	120 hp
Number of Tools	30
Rotor Diameter	18"
Rotor Speed	2,400 rpm
Rotor Bearing Size (mm)	ST65
Motor(s)	1 x 107V

BUILT FOR LIFE
ENGINEERED FOR SUCCESS

The BLACKHAWK® mulcher tackles vegetation management and land clearing needs in stringy, fibrous, dense, and fast-growing material typically found in regions with higher temperatures and longer growing cycles.

The BLACKHAWK® mulcher is designed to quickly process stubborn standing and felled vegetation, ensuring no unprocessed material is left behind.

PERFORMANCE

- ✦ Utilizing shear bars and knife tools, the BLACKHAWK® creates consistent chips on the first pass
- ✦ The cutting chamber is designed to process material going forwards and back dragging without leaving unprocessed material
- ✦ 18" rotor spools up quickly and minimizes wait time

EFFICIENCY

- ✦ Compact body design and increased visibility improves carrier operating and handling
- ✦ Broadcasting front discharge mitigates the need for multiple passes
- ✦ Simplified hydraulic system minimizes heat generation

DURABILITY

- ✦ Replaceable bolt-on shear bar and wear liner
- ✦ Rotate to increase life
- ✦ High strength steel body construction to withstand the rigors of everyday use
- ✦ Adjustable pin-on push bar to guide cut material

OPTIONAL ADD ONS:

FECUN® Hydraulic Cooler

Designed to be mounted on CTL and Skid Steer to maintain the hydraulic fluid at optimal temperature and viscosity.

FECUN® Polycarbonate Door

Form-fit 1/2" polycarbonate door required for mulching applications. Our replacement windows are formed to duplicate the OEM glass shape.

